

VÄRINÄNVAIMENTIMET

Värinänvaimennin


Materiaali

Ruostumaton teräs SS 2322-02 / SS 2346-02


Öljynkestävä nitrilikumi, kovuus 52 shorea




TYYPPI 50




TYYPPI 51




TYYPPI 52



TYYPPI 53



TYYPPI 54



TYYPPI 50

Tuotenro	D mm	H mm	M mm	L mm	s mm	Maks. kuormitus N
19-5002015	20	15	M6	18	2	210
19-5003020	30	20	M8	15	2	490
19-5004025	40	25	M8	20	3	840
19-5005030	50	30	M10	27	3	1330

TYYPPI 51

Tuotenro	D mm	H mm	M mm	L mm	s mm	s1 mm	Maks. kuormitus N
19-5102015	20	15	M6	18	2	4	210
19-5103020	30	20	M8	20	2	6	490
19-5104025	40	25	M8	22	3	7	840
19-5105030	50	30	M10	27	3	8	1330

TYYPPI 52

Tuotenro	D mm	H mm	M mm	L mm	s mm	s1 mm	Maks. kuormitus N
19-5202015	20	15	M6	-	2	4	210
19-5203020	30	20	M8	-	2	6	490
19-5204025	40	25	M8	-	3	7	840
19-5205030	50	30	M10	-	3	8	1330

TYYPPI 53

Tuotenro	D mm	H mm	M mm	L mm	s mm	Maks. kuormitus N
19-5302015	20	15	M6	18	2	210
19-5303020	30	20	M8	20	2	490
19-5304025	40	25	M8	25	3	840
19-5305030	50	30	M10	27	3	1330

TYYPPI 54

Tuotenro	D mm	H mm	M mm	L mm	s mm	s1 mm	Maks. kuormitus N
19-5402015	20	15	M6	-	2	4	210
19-5403020	30	20	M8	-	2	6	490
19-5404025	40	25	M8	-	3	7	840
19-5405030	50	30	M10	-	3	8	1330